

GCE

Physics B

H557/01: Fundamentals of physics

Advanced GCE

Mark Scheme for Autumn 2021

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

© OCR 2021



1. Annotations available in RM Assessor

Annotation	Meaning
BOD	Benefit of doubt given
CON	Contradiction
×	Incorrect response
ECF	Error carried forward
LI	Level 1
L2	Level 2
L3	Level 3
TE	Transcription error
NBOD	Benefit of doubt not given
POT	Power of 10 error
^	Omission mark
SF	Error in number of significant figures
V	Correct response
?	Wrong physics or equation



2. Abbreviations, annotations and conventions used in the detailed Mark Scheme (to include abbreviations and subject-specific conventions).

Annotation	Meaning	
I	alternative and acceptable answers for the same marking point	
reject	Answers which are not worthy of credit	
not	Answers which are not worthy of credit	
Ignore	Statements which are irrelevant	
Allow	Answers that can be accepted	
()	Words which are not essential to gain credit	
_	Underlined words must be present in answer to score a mark	
ECF	Error carried forward	
AW	Alternative wording	
ORA	Or reverse argument	



Section A: MCQs

Question	Answer	Marks	Guidance
1	В	L	
2	D	L	
3	A	M	
4	В	L	
5	С	M	-
6	D	M	
7	D	L	
8	В	L	-
9	В	L	-
10	В	M	
11	С	M	
12	A	M	·
13	В	30L	-
14	A	L	
15	D	/ L	-
16	D	M	
17	A	Н	
18	С	Н	
19	C	Н	
20	A	M	
21	A	M	
22	В	Н	
23	В	M	
24	В	Н	
25	В	L	
26	A	Н	
27	C	L	
28	B B	Н	
29	В	M	
30	A	Н	
	Total	30	



Section B

Qu	estion	Answer	Marks	Guidance
31	(a)	method: diameter of atom = Circumference/[no. atoms + spaces] \checkmark = $\pi D / [2 \times 19]$ OR = $3.5\pi / 38$ (nm) \checkmark	L	correct counting to 38 [atoms + spaces]
		evaluation: = 0.29 OR 0.3 (nm)	M	value of 0.58 nm (from using radius instead of diameter in circumference calculation) max 1; not 0.6 or 0.58 if scaling method used
			34	other methods acceptable including measuring diameter of circle and individual atom leading to evaluation in the range 0.23 to 0.29nm: • correct ratio of measured length of arrow / 3.5nm ✓ • measured diameter of atom / ratio ✓ • evaluation in range 0.23 to 0.29nm OR correctly rounded to 0.2 or 0.3nm ✓
		Total	3	

Qı	uestio	n	Answer	Mark s	Guidance
32	(a)		12½ waves per 1 ms means f _{max} ≈ 12500 Hz and need 2 samples per cycle	L	need to identify f_{max} for mark do not allow 25kHz/2 = 12.5kHz for f_{max} not just "sampling needs to be at least double the highest frequency" or statements of Nyquist
32	(b)		V _{total} / V _{noise} ≈ 140 / 0.4 = 350	L	Allow estimates in range 340 to 360
			$2^{\text{bits}} > 350$ $2^9 = 512 \text{ suggest } 9 \text{ bits sample}^{-1} \checkmark$	M	need to show $2^8 = 256$ or $2^9 = 512$ or $log_2(350) = 8.45$ leading to 9 (bits sample ⁻¹) for second mark not just quoting bits = $log_2(V_{total}/V_{noise})$ from data booklet
				20)	Tiot just quoting bits – 10g2(viotal/vioise) Homidata bookiet
			Total	3	

Q	uesti	on	Answer	Marks	Guidance
33	(a)		wavelengths are shortened OR they are blue-shifted	L	Must have idea of change
			because these galaxies are approaching (Milky Way) ✓	L	Allow emitted waves are bunched up not just "because of Doppler effect"
33	(b)	(i)	1000/1.9 / [4 × 10 ⁴ /660] ✓	M	Allow first mark for correctly calculating both gradients – units not required for mark 1929 gradient in range 519 to 526 1998 gradient in range 60.6 to 61.5
			(= 526 / 60.6) = 8.7 ✓	М	Allow evaluation in range 8.4 to 8.7
				34)	Allow a valid comparison with completed calculation using 8 x 1998 gradient value or 1929 value / 8 for the second mark
				4)	Allow max 1 for a correct evaluation in the range > 8 , ≤ 9 using correct method but incorrect values from graphs.
33	(b)	(ii)	age = 1/H₀ ✓	Н	method Allow 1 / gradient OR in numbers Allow ecf from gradient in b(i) for this mark
			= $[660 \times 3.1 \times 10^{22}]/[4 \times 10^{7}]$ s = $5.1 \times 10^{17}/3.2 \times 10^{7}$ years = $16 (\pm 2) \times 10^{9}$ (years)	Н	evaluation of show that.
			Total	5	



Qı	uesti	on	Answer	Marks	Guidance
34	(a)		$N = A \times t_{1/2} / \ln 2$ OR = $8.5 \times 10^6 \times 60 \times 24 \times 3600 / 0.693 \checkmark$ = 6.4×10^{13}	L	method evaluation
34	(b)		absorbed dose = $N_0/2 \times 35 \times 10^3 \times 1.6 \times 10^{-19} \times 1/0.05$ \checkmark = 3.6 (Sv)	M	method mark for using energy deposited per unit mass Allow 3.4 Sv using $N_0 = 6 \times 10^{13}$ for 2 marks Allow ecf from 34(a) when N_0 rounds to >6 and <7 Allow 1 mark for 7.2 Sv for only ½ decay
34	(c)		cells nearer seed will receive higher dose than farther away / to give more even irradiation / dose will decay away from the seed by γ-ray absorption ✓	L	any valid point e.g. spread over greater volume further away Allow spreads out over larger (surface) area further away Allow valid use of 1/R ² and / or exponentially
			Total	5	

Qı	Question		Answer		Guidance
35	(a)		e.g. lines on graph OR $e^{-1} = 0.37$	Н	evidence of finding f when $E = kT$
			T = 1300 (K) ✓	Н	accept answers in range 1100 to 1500 (K) if first mark awarded
35	(b)		the average molecule has energy <i>kT</i> and so will be able to perform the process ✓	_	completion: allow very few collisions occur with a pair of molecules with less than energy <i>kT</i>
			Boltzmann factor $e^{-20} \approx 2 \times 10^{-9}$ so only a small fraction of molecules have sufficient energy but make many attempts each second / high collision frequency giving a significant rate	M	significant rate at $T/20$: OR Boltzmann tail contains molecules that have much higher than average energy by "getting lucky" / gaining energy from multiple consecutive collisions by chance from the thermal chaos
			Total	4	
			Total section B	20	



Section C

Question	Answer	Marks	Guidance
36 (a) *	Level 3 (5–6 marks)		Allow labelled diagrams or graphs
	Marshals argument in a clear manner and includes clear explanation of all strands including: • circuit diagram with scaled components and correct symbols • methodology of readings to be taken • analysis to find r There is a well-developed line of reasoning which is clear and logically structured. The information presented is relevant and substantiated. Level 2 (3–4 marks) Covers all strands at a superficial level and does not include enough depth for level 3. There is a line of reasoning presented with some structure. The information presented is relevant and supported by some evidence. Level 1 (1–2 marks)	LL MM HH	Indicative scientific points in the three strands may include: • cell and variable resistor in range 10-100 Ω / at least five discrete resistors to give range 10-100 Ω • series circuit, possibly with switch to rest cell • Voltmeter in parallel with the variable load resistor / cell range: up to 10V max • Ammeter in series range: mA up to 1Amp methodology of readings • measure V on open circuit no load current i.e. e.m.f. • rest cell with switch between readings • connect max load resistance measure V, I tabulate • decrease load resistance repeat V, I readings • adjust load so that readings in V / I roughly evenly spaced • repeat until load on cell is 0 Ω / cell is shorted to measure
	Makes at least two independent points (possibly from only one strand), that are relevant to the argument but does not link them together and shows only superficial engagement with the argument. There is an attempt at a logical structure with a line of reasoning. The information is in the most part relevant. O marks No response or no response worthy of credit		 analysis to find r plot V on y-axis vs I on x-axis plot straight line of best fit r = gradient of line or from r = [E-V] / I calculations draw best fit lines of max and /or min gradient to estimate uncertainty in r

Q	uesti	on	Answer	Marks	Guidance
36		(i)	$Q = It \text{ so } A \times h = 1 A \times 3600 \text{ s} = 3600 \text{ As or } 3600 \text{ C} \checkmark$ OR	L	
36		(ii)	charge = current × time \checkmark curving up to about $0.18 \pm 0.2 \Omega$ by about 60 mins \checkmark levelling off then increasing again to 0.27Ω \checkmark If graph not drawn credit any one correct calculation based on $r = [4.2 - V] / 4.5$ including $[4.2 - 3.0] / 4.5 = 0.27 \Omega$ for final value	H	Not just Q = It p.d./v 3 0.3 r/Ω 0.2 1 0.1 0.1 0.1 0.1 0.1 0.1
36	(b)	(iii)	$N=It/[N_A \times e] = 4.5 \times 2 \times 3600/[6.0 \times 10^{23} \times 1.6 \times 10^{-19}]$ = 0.3(4) (moles) \checkmark OR $N=It/[N_A \times e]$ = 4.5 × 116 × 60 / [6.0 × 10 ²³ × 1.6 × 10 ⁻¹⁹] \checkmark = 0.33 (moles)	S&C S&C	estimate method Allow approximation <i>t</i> = 2 hours evaluation
			Total	11	

Que	estio	n	Answer	Marks	Guidance
37 ((i)	(tilting the runway slightly so that) component (of gravity) down the slope balances friction OR so that there is no resultant force on the trolley at the experimental speed ✓	L	Accept (downward slope can ensure it) maintains constant speed
37 ((b)	*	Level 3 (5–6 marks) Marshals argument in a clear manner and includes clear explanation of all strands including: • conservation of momentum check • conservation of kinetic energy check • forces acting on each trolley There is a well-developed line of reasoning which is clear and logically structured. The information presented is relevant and substantiated. Level 2 (3–4 marks) covers all strands at a superficial level and does not include enough depth for level 3. There is a line of reasoning presented with some structure. The information presented is relevant and supported by some evidence.	HH H S&C	Indicative scientific points may include: expect measurements from tapes to be to ± 1 mm accuracy i.e. tape A before: 79 to 81; tape A after:39 to 41; tape B after 119 to 121. Allow use of less than 5 dot strip as long as measured length leads to evaluation in range. conservation of momentum check • momentum before = 0.9 × 0.8 = 0.72 kg m s ⁻¹ • after = [0.9 × 0.4 + 0.3 × 1.2] = 0.72 kg m s ⁻¹ sensibly conserved / to within the limits of uncertainty measurements comment that momentum is conserved in (all) collisions and should be conserved here. conservation of kinetic energy check • k.e. before = ½ × 0.9 × [0.8]² = 0.288 J • k.e. after = ½ × 0.9 × [0.4]² + ½ × 0.3 × [1.2]² = 0.072 + 0.216 = 0.288 J • sensibly conserved / to within limits of uncertainty measurements • so perfectly elastic collision • comment that kinetic energy is not always conserved in collisions • comment that kinetic energy is conserved in elastic collisions

Q	uesti	on	Answer	Marks	Guidance
			Level 1 (1–2 marks) Makes at least two independent points (possibly from only one strand), that are relevant to the argument but does not link them together and shows only superficial engagement with the argument. There is an attempt at a logical structure with a line of reasoning. The information is in the most part relevant. O marks No response or no response worthy of credit		forces acting on each trolley • forces are equal and opposite OR • some version of N3 backwards on A, forwards on B • \rightarrow $F_B = \Delta mv / \Delta t = 0.3 \times 1.23 / 0.06 = 6.2 N to right OR • \leftarrow F_A = 0.9 \times [0.41 - 0.82] / 0.06 = 6.2 N to left$
37	(c)	(i)	volume flow rate OR Av must remain constant \checkmark by calculation for 1.0 s: $v_1\pi [0.075]^2/4 = v_2\pi [0.025]^2/4$ gives $9v_1 = v_2$ \checkmark OR at F diameter is $\frac{1}{3}$ of value at E so A is $\frac{1}{9}$	M S & C	Allow water is incompressible expect numerical argument completed OR $A \propto D^2$ OR $A \propto R^2$ with $[1/3]^2 = 1/9$
37	(c)	(ii)	$\pi D_1^2 v_1/4 = 0.02 \text{ OR } v_1 = 0.020 \times 4 / [\pi D_1^2] $ $= 4.5(3) (\text{m s}^{-1}) $ $\text{OR } v_1 = 0.020 \times 4 / [9 \pi \times 0.025^2] ; = 4.5(3) (\text{m s}^{-1})$	S&C S&C	method evaluation Max 1 mark if diameter used for radius
37	(c)	(iii)	rate of change of momentum of water in nozzle= $\Delta m v / \Delta t \sqrt{1}$ = 20 × (9-1) v_1 = 20×8×4.53 = 72(4)(N)	H S&C	Method – no credit for just writing = $\Delta mv/\Delta t$ from formula sheet evaluation
			Total	13	

Q	Question		Answer	Marks	Guidance
38	(a)	(i)	$E = ke/r^2 = 8.98 \times 10^9 \times 1.6 \times 10^{-19} / [40 \times 10^{-12}]^2$ $= 0.90 \times 10^{12} (V \text{ m}^{-1})$	L	Allow just $E = ke/r^2$ OR correct substitution for method mark allow use of $k = 9x10^9$ leading to 0.9×10^{12} evaluation of show that : allow 0.898×10^{12}
	(a)	(ii)	expect two valid checks with 2 approx = numerical values ✓✓ OR 0.9 TV m ⁻¹ @ 40 pm becomes 0.9/2² = 0.22 TV m ⁻¹ @ 80 pm two values here ✓✓	MM	check: Er^2 = sensibly constant in range [1.4 to 1.5] x10 ⁻⁹ Max 1 mark if one value just outside range Max 1 mark only for general statement: as r doubles E becomes x $\frac{1}{4}$ OR for 1 value of Er^2 Allow full credit for correct calculation without units
38	(a)	(iii)	area represents p.d. OR potential difference OR $\Delta V \checkmark$ 1 big sq = 0.2x10 ¹² x 20x10 ⁻¹² = 4 V and about 5 ± ½ big squares ≈ 20 ± 2 V OR = $\Delta ke/r = 9x10^9x1.6x10^{-19}x [^1/52x10^{-12} - ^1/160x10^{-12}] \checkmark$ = [27.7 - 9] = 18.7 V	H S&C	not unit of V evaluation by counting squares allow units not needed here if area ≡ voltage given already
38	(b)	(i)	method: $m v^2 / r = k e^2 / r^2 \rightarrow \frac{1}{2} m v^2 = k e^2 / 2 r \checkmark$	Н	requires algebraic argument
38	(b)	(ii)	$E_{\text{total}} = \frac{1}{2} k e^2 / r - k e^2 / r = -\frac{1}{2} k e^2 / r$ graph is mirror image i.e E_{kinetic}	M	must be clear that E potential = $-ke^2/r$ energy / eV 10 Note the clear that E potential energy potential energy potential energy potential energy



nce
uantisation any energy or nd there would be no specific spectrum
re electron to ∞)
spec

Q	Question		Answer	Marks	Guidance
39	(a)	(i)	flux loops want to shorten / magnet tries to align parallel to flux between coils 1 and 2 (at about $\theta = 30^\circ$) /flux lines leave N pole of rotor at an angle which exerts a turning moment to right \checkmark	L	Allow coil 1 is a S and will attract the N pole of the rotor (so this force will turn the rotor clockwise) not flux lines leave S pole of rotor radially which exerts no turning moment in this position
39	(a)	(ii)	anticlockwise path completed loop through the upper ¹/₃ of stator ring ✓	L	only one field line loop expected
39	(b)		1: to make a stronger (stator) field / flux OR increase permeance (of flux path) 2: to reduce eddy currents / heat losses 3: to get more flux for the same (stator) coil current OR as air gaps reduce permeance (of magnetic circuit) / as air gaps reduce permeance (of magnetic circuit)	M M	Allow reduce reluctance of flux path Must have correct technical term – e.g. permeance / reluctance
39	(c)		1: alter the frequency of switching (coils) ✓ 2: alter magnitude of current (in stator coils) / (supply) voltage ✓	Н	allow for second mark pulse the switched supply voltage / current to stator coils by pulse width modulation PWM / on:off ratio will determine moment
			Total	9	

Q	Question		Answer	Marks	Guidance
40	(a)	(i)	P ∝ 1/V ✓	L	Allow in words e.g. just "inverse proportionality"
			$V \propto T$ AND $P \propto T$ (OR θ + 273)	M	Allow in words but response must either make reference to T or <u>absolute</u> temperature / <u>Kelvin</u> temperature
40	(a)	(ii)	e.g. $PV = c_1 = c_2T = kNT = NkT$	M	Must have PV/T = constant OR PV=constant x T leading to pV=NkT allow ecf if correctly combined to an (incorrect) equation involving k
40	(a)	(iii)	$k = 101 \times 10^{3} \times 22.4 \times 10^{-3} / [6.02 \times 10^{23} \times 273]$ = $1.377 \times 10^{-23} (J K^{-1}) = 1.38 \times 10^{-23} (J K^{-1})$	M	evaluation to 4sf so that it shows correct conversions & subs rounded to 3sf for final answer not just quote the datasheet value alone for which no credit
40	(b)	(i)	$ \sqrt{c^2} = \sqrt{[3NkT/m]} \text{OR} \sqrt{c^2} = \sqrt{[3RT/m]} \checkmark $ $ = \sqrt{[3 \times 6.02 \times 10^{23} \times 1.38 \times 10^{-23} \times 300/4.0 \times 10^{-3}]} $ $ \text{OR} = \sqrt{[3 \times 8.31 \times 300/4.0 \times 10^{-3}]} $ $ =1.37 \times 10^3 $	M	method Allow in algebra or substituted numbers evaluation accept 1.4 × 10 ³ (ms ⁻¹)
40	(b)	(ii)	Any two points : $\sqrt{\ }$ high collision frequency $/ \approx 10^9 \text{s}^{-1}$ OR small mean free path $/ \approx 10^{-7} \text{m}$ random change in direction after collision OR random path gives slow diffusion or spread OR mean diffused distance = $\sqrt{N} x \approx \text{few cm per minute}$	L M	not scent molecules more massive travel slower not sensitivity of nasal detection Allow diagram for full marks if clearly explained and annotated Allow reference to Brownian motion for one of two points
			Total	8	



Q	Question		Answer	Marks	Guidance
41	(a)	(i)	$\Delta m = [1.008665 - \{1.007276 + 0.000549\}] = 0.00084 \text{ u } \checkmark$	L	find mass defect in u
			= 0.78(2) (MeV) ✓	L	convert to MeV
41	(a)	(ii)	"missing" energy / momentum was carried by an (anti)neutrino / a particle of tiny rest mass and zero charge	M	Allow Energy (of beta particle) is shared with (anti)neutrino / a particle of tiny rest mass and zero charge
41	(a)	(iii)	$A = \lambda N = \ln 2 / t_{1/2} \times 10^4$	M	Allow alternative method – e.g. calculate <i>N</i> remaining after 1 s (for 1 mark) and subtract from 10 ⁴ (for second mark)
			= 10 or 11 (10.7 s ⁻¹) \checkmark	M	evaluation do not penalise non-integer values
41	(a)	(iv)	d quark changes → u quark ✓	34	Allow udd → uud
41	(b)		stable neutrons exist in nuclei of light elements very close to <i>N</i> = <i>Z</i> OR <i>N</i> / <i>Z</i> = 1 ✓	M	Allow vice-versa – e.g. unstable neutrons exist for nuclei where N/Z > 1
					Allow worded explanation, for example with reference to concept of "neutron rich"
					Allow unstable nuclei become stable by beta emission which increases Z to become closer/equal to N
					Not just "they are stable"
			Total	7	
			Total section C	60	
			Total sections B & C	80	

OCR (Oxford Cambridge and RSA Examinations)
The Triangle Building
Shaftesbury Road
Cambridge
CB2 8EA

OCR Customer Contact Centre

Education and Learning

Telephone: 01223 553998 Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

